



TAT240

4G LTE CAT 1 asset tracker with
Tamper detection


Quick Manual v1.1

CONTENT


Know your device.....	3
Set up your device	4
PC Connection (Windows).....	5
How to install USB drivers (Windows)	5
Configuration.....	6
Quick SMS configuration.....	8
Tamper scenario	10
Mounting recommendations.....	12
Status LED indications	13
Basic characteristics	13
Safety information	16
Certification and Approvals	17
Warranty	18
Warranty disclaimer.....	18

KNOW YOUR DEVICE


TOP VIEW




SIDE VIEW



SIDE VIEW




MAGNETIC HOLDER WITH TAMPER DETECTION




SET UP YOUR DEVICE

HOW TO INSERT MICRO-SIM CARD AND CONNECT THE BATTERY



1 COVER REMOVAL

Remove the cover.




2 MICRO-SIM CARD INSERT

Insert **Micro-SIM** card as shown with **PIN request disabled** or read our [Wiki](#)¹ how to enter it later in [Teltonika Configurator](#)². Make sure that **Micro-SIM card cut-off corner** is pointing forward to slot.


¹ wiki.teltonika-gps.com/view/TAT240_Security_info

² wiki.teltonika.lt/view/Teltonika_Configurator



3 TURN ON

Flip the switch to ON.



4 ATTACHING COVER BACK

After configuration, see [PC Connection \(WINDOWS\)](#)¹. When it is done, reattach the cover and push it in place.

¹ Page 5, "PC Connection (Windows)"

PC CONNECTION (WINDOWS)

1. Power-up TAT240 device. LED should start blinking, see “LED indications”¹.
2. Connect your device to computer using **Micro-USB** cable:
 - You will need to install USB drivers, see “How to install USB Drivers (WINDOWS)”²
3. You are now ready to use the device on your computer.

¹ Page 11 “LED indications”

² Page 5, “PC Connection (Windows)”

HOW TO INSTALL USB DRIVERS (WINDOWS)

1. Please download COM port drivers from [here](#)¹.
2. Extract and run **TeltonikaCOMDriver.exe**.
3. Click **Next** in driver installation window.
4. In the following window click **Install** button.
5. Setup will continue installing the driver and eventually the confirmation window will appear. Click **Finish** to complete the setup.

¹ wiki.teltonika-gps.com/images/d/d0/TeltonikaCOMDriver.zip

CONFIGURATION

At first TAT240 device will have default factory settings set. These settings should be changed according to the users needs. Main configuration can be performed via [Teltonika Configurator](#)¹ software. Get the latest **Configurator** version from [here](#)². Configurator operates on **Microsoft Windows OS** and uses prerequisite **MS .NET Framework**. Make sure you have the correct version installed.


¹ wiki.teltonika-gps.com/view/Teltonika_Configurator


² wiki.teltonika-gps.com/view/Teltonika_Configurator_versions

MS .NET REQUIREMENTS

Operating system	MS .NET Framework version	Version	Links
Windows Vista			
Windows 7			
Windows 8.1	MS .NET Framework 4.6.2	32 and 64 bit	www.microsoft.com ¹
Windows 10			


¹ dotnet.microsoft.com/en-us/download/dotnet-framework



Downloaded Configurator will be in compressed archive. Extract it and launch Configurator.exe. After launch software language can be changed by clicking  in the right bottom corner.











Configuration process begins by pressing on connected device.



After connection to Configurator **Status window** will be displayed.

Various **Status window**¹ tabs display information about **GNSS**², **GSM**³, **I/O**⁴, **Maintenance**⁵ and etc. TAT240 has one user editable profile, which can be loaded and saved to the device. After any modification of configuration the changes need to be saved to device using **Save to device** button. Main buttons offer following functionality:

-  **Load from device** – loads configuration from device.
-  **Save to device** – saves configuration to device.
-  **Load from file** – loads configuration from file.
-  **Save to file** – saves configuration to file.
-  **Update firmware** – updates firmware on device.
-  **Read records** – reads records from the device.
-  **Reboot device** – restarts device.
-  **Reset configuration** – sets device configuration to default.

Most important configurator section is **GPRS** – where all your server and **GPRS settings**⁶ can be configured and **Data Acquisition**⁷ – where data acquiring parameters can be configured. More details about TAT240 configuration using Configurator can be found in our [Wiki](#)⁸.

¹ wiki.teltonika-gps.com/view/TAT240_Status_info

² wiki.teltonika-gps.com/view/TAT240_Status_info#GNSS_Info

³ wiki.teltonika-gps.com/view/TAT240_Status_info#GSM_Info

⁴ wiki.teltonika-gps.com/view/TAT240_Status_info#I2FO_Info

⁵ wiki.teltonika-gps.com/view/TAT240_Status_info#Maintenance

⁶ wiki.teltonika-gps.com/index.php?title=TAT240_GPRS_settings

⁷ wiki.teltonika-gps.com/index.php?title=TAT240_Data_acquisition_settings

⁸ wiki.teltonika-gps.com/index.php?title=TAT240_Configuration

QUICK SMS CONFIGURATION

Default configuration has optimal parameters present to ensure best performance of track quality and data usage. Quickly set up your device by sending this SMS command to it:

```
« setparam 2001:APN;2002:APN_username;2003:APN_password;2004:Domain;2005:Port;2006:0»
```

1

2

3

4

5

6


Note: Before SMS text, two space symbols should be inserted.

GPRS SETTINGS:

- 1 2001 – APN
- 2 2002 – APN username (if there are no APN username, empty field should be left)
- 3 2003 – APN password (if there are no APN password, empty field should be left)

SERVER SETTINGS:

- 4 2004 – Domain
- 5 2005 – Port
- 6 2006 – Data sending protocol (0 – TCP, 1 – UDP)



DEFAULT CONFIGURATION SETTINGS

MOVEMENT DETECTION:



DEVICE MOVEMENT
will be detected by
accelerometer

DEVICE MAKES A RECORD ON STOP IF:



28800
Seconds passes

DEVICE MAKES A RECORD ON MOVING IF ONE OF THESE EVENTS HAPPEN:




28800
Seconds passes

Time intervals and default I/O elements can be changed by using Teltonika [Configurator](#)¹.

¹ wiki.teltonika-gps.com/view/Teltonika_Configurator

IMPORTANT CONFIGURATION NOTES



We strongly recommend testing the network connection from device to the server before adjusting TAT240 configuration to your needs. Use the following steps to perform this test:

- Configure these parameters: APN, server Domain and server Port;
- Save configuration to the device by clicking on a Save to device button;
- Initiate connection by pressing the Test Connection button.

At this point, TAT240 will create one high-priority record and initiate connection to the server immediately.

If connection was not initiated, it can mean any of the following:

- Improperly inserted SIM Card
- Incorrect values are set to these fields: APN, Domain or Port;
- GPRS functionality disabled by GSM provider;
- No GSM coverage;
- Server cannot be reached.

Try solving this problem before proceeding with further device configuration.

Tracking Scenarios

Tracking Mode

None Periodic

Scheduler

Tracking Options

On stop

On Stop periodic tracking

OFF ON

On Stop event record

Disable Enable

On Stop (s) 28800

On Move

On Move periodic tracking

OFF ON

On Move event record

Disable Enable

On Moving (s) 28800

Time Zone UTC+00:00

Record timestamp shift

Disable Enable

On Stop detection time (s) 600

On Move detection time (s) 20

On Stop periodic tracking - enable or disable periodic data sending when device is On Stop. Device will generate and send normal record with event ID 0 and movement AVL ID 240 with a value of 0.

On Stop event record - enable or disable record sending when device switches tracking scenario from On Move to On Stop. To trigger this event **On Stop detection time timer** needs to reach set value. Once event is triggered GNSS module will wake up and obtain GNSS fix. Record will have AVL event 240 with a value of 4 that means "Movement event - On Stop".

On Move periodic tracking - enable or disable periodic data sending when device is On Move. Device will generate and send normal record with event ID 0 and movement AVL ID 240 with a value of 1.

On Move event record - enable or **disable** record sending when device switches tracking scenario from On Stop to On Move. To trigger this event **On Move detection time** timer needs to reach set value. Once event is triggered device will wake up and will trigger one of two records:

1 - if last record did not have a GNSS fix, GNSS module will be turned on and fix obtained.

2 - if last record had a valid GNSS fix, GNSS module will not be turned on and record will contain last good coordinates.

On Stop detection time (s) configurable amount of time until device switches to On Stop periodic tracking. Device needs to

be stationary for configured amount of time to change state. Movement interrupts will reset this timer.

On Move detection time (s) configurable amount of time until device switches to On Move periodic tracking. Instant movement will not change tracking scenario to On Move. Device needs to be interrupted **at least once every 5 seconds** during the configured time to change tracking scenario to On Move.

MAIN RULES OF SETTING SCHEDULE

Tracking Scenarios

Tracking Mode

None Periodic

Scheduler

Time zone UTC+00:00

Record timestamp shift

Disable Enable

On Stop detection time (s) 600

On Move detection time (s) 20

Scheduler

Day of the Week	Seconds per day	1st	2nd	3rd	4th	5th	6th	7th
Monday	1	12:00	12:00	12:00	12:00	12:00	12:00	12:00
Tuesday	1	12:00	12:00	12:00	12:00	12:00	12:00	12:00
Wednesday	1	12:00	12:00	12:00	12:00	12:00	12:00	12:00
Thursday	1	12:00	12:00	12:00	12:00	12:00	12:00	12:00
Friday	1	12:00	12:00	12:00	12:00	12:00	12:00	12:00
Saturday	1	12:00	12:00	12:00	12:00	12:00	12:00	12:00
Sunday	1	12:00	12:00	12:00	12:00	12:00	12:00	12:00

- Intervals between different times must be at least 6 minutes;
- Days of the week must be selected and highlighted for the device to send records according to the set schedule.

More details about device configuration using Teltonika Configurator can be found in the Teltonika wiki knowledge base wiki.teltonika-gps.com

TAMPER SCENARIO

For some applications or for general convenience an attachable magnetic holder as known as a Tamper is developed for TAT devices. It adds some additional functionalities to the device that will be described in this paragraph.

The device is able to detect 4 Tamper states. Tamper event record has AVL ID 20019 (2 bytes in size) with the following possible values:

- 0: Holder is removed. This state is detected when the device is **without holder**.
- 1: Central is attached. This state is detected when **only central magnet** is added.
- 2: Attached to metal surface. This state is detected when the device is **with holder and central magnet**.
- 3: Removed from metal surface. This state is detected when the device is **with holder only**.

IMPORTANT

Make sure the device can detect the holder. Otherwise, attached holder will still result in “Holder removed” state and not “Removed from surface”

CONFIGURATION AND FUNCTIONALITIES

Firstly, it is important to check mechanical configuration of the whole unit. The main steps are:

1. Make sure the central magnet's polarity is in the right direction. To check this, put central device on the holder only (without attached to the device). If the holder pushes it out, it means its polarity direction is correct. Otherwise, flip the magnet.
2. Make sure the device detects the holder itself. It can be checked in the log on first start by seeing the print: “New state: [Holder removed -> Removed from surface].”
3. If it is still not detected, try rotating the holder and put on again. If it still fails, try unscrewing the holder's screws to check magnets' presence. The small magnets should be placed in a way that they try to push the screws out.

THE MAIN CONFIGURATION TABLE

Tamper detection lets user to turn off / on Tamper feature completely.

Tamper detection event allows user to select desired Event when device should report about changed state. More than one option is available.

Tamper Detection	
Disable	Enable
Tamper Detection Event	
Removed	Central Attached
Attached to surface	Removed from surface
Record type	
Event only	Event and Fix
Activate Recovery mode	
None	Removed
Central Attached	Attached to surface
Removed from surface	

RECORD TYPE

This option controls the way records are generated during tamper event:

- **Event only:** wake up modem and send a quick record with last known coordinates.
- **Event and Fix:** wake up modem and send a quick record with last known coordinates, then device does a full GNSS scan and sends another record with full data.

Activate Recovery mode allows user to select on what event recovery mode should be activated. When tamper state has changed to selected event, the device generates Tamper alarm record and starts Recovery Mode immediately.

Note: currently it is only possible to select a single option for Recovery mode activation.

RECORD GENERATION

Tamper records will be generated separately from other records as soon as event is detected. It is important to configure precise events when expecting certain events to happen.

For example: if user is using Tamper to attach TAT to a surface and want to detect its removal from it, "Removed from surface" option should be selected. In extreme case, if the device is removed not only from surface but the whole holder is separated, "Removed" can be selected to detect it.

It should be noted that **event records** will be send with **last known coordinates**. In order to also receive a record with coordinates, switch **Record type** parameter to **Event and Fix**. If user wants the device to start alarming rapidly about some kind of tamper event it is advisable to use Tamper scenario with Recovery Mode activation with short Recovery mode period configured for fast reports.

Parameter IDs to be added to wiki.teltonika-gps.com/view/TAT240_Parameter_list

PARAMETER NAME	ID	VALUES
Tamper Detection	290	0 - disabled 1 -enabled
		0 - Invalid value 1 - Removed 2 - Attached 4 - Attached on surface 8 - Removed from Surface
Tamper Detection Event	291	Other values are a sum of different state numbers. For example, if you want to configure Removed from Surface and Removed together, just add state numbers and the value will be 9. To detect all states, value is 15

Record type	292	0 - Event only 1 - Event and Fix
Recovery Mode		0 - None 1 - Removed
Triggering Tamper Event	293	2 - Attached 3 - Attached on surface 4 - Removed from surface

MOUNTING RECOMMENDATIONS

We recommend mounting the TAT240 in such a way that the GNSS antenna is pointed at the sky and the device itself is not covered by various obstructions that would interfere with the reception of the GNSS fix.

STATUS LED INDICATIONS

BEHAVIOUR	MEANING
On	Start-up and self-tests
Off	Device is in sleep mode or turned off
Blink every 5 seconds	Device is working, modem turned on.

BASIC CHARACTERISTICS

PRODUCT

Model name	TAT240-QJIB0
------------	--------------

MODULE

Name	Quectel EG915U-EU with Teltonika TM2500
Technology	LTE(Cat1)/2G(GSM/GPRS)/GNSS/BLUETOOTH® LE

GNSS¹

GNSS	L1: GPS, GLONASS, GALILEO, BEIDOU, SBAS*, QZSS*, DGPS*, AGPS*
Receiver	33 tracking channel 99 acquisition channel
Tracking sensitivity	-165 dBm
Position accuracy	< 2.5 m CEP

CELLULAR

2G bands	GSM: B2/B3/B5/B8
4G bands	LTE FDD: B1/B3//B5/B7/B8/B20/B28
Data transfer	LTE FDD (CAT 1): Max. 10 Mbps (DL) / Max. 5 Mbps (UL); GSM (GPRS): Max. 85.6 Kbps (DL) / Max. 85.6 Kbps (UL)"
Transmit power	Class 4 for GSM850/900: 33±2dBm Class 1 for GSM1800/1900: 30±2dBm Class 3 for LTE-FDD: 23±2dBm
Data support	SMS (TEXT), Network protocols (TCP,UDP,TLS, EGTS, MQTT ²)

¹ Optional modes available with custom firmware applications, for more information contact your sales manager.

² Optional protocols available with custom firmware applications, for more information contact your sales manager.

POWER

Battery	2200mAh, 2S, extremely low self-discharge Li-SOCI2 batteries 7.2V, Non-rechargeable
---------	---

BLUETOOTH® TECHNOLOGY

Specification	4.2 + LE
Supported peripherals	EYE Sensors, EYE Beacons (recovery mode only), Universal Bluetooth® LE sensors support

PHYSICAL SPECIFICATION

Dimensions	78 x 63 x 28 mm (L x W x H)
Weight	115g. (with 2 cells battery)

OPERATING ENVIRONMENT

Operating temperature (with battery)	-35 °C to +75 °C
Storage temperature (with battery)	-40 °C to +85 °C (Recommended max. 30°C)
Operating humidity	5% to 95% non-condensing
Ingress Protection Rating	IP68
Battery discharge temperature	-60 °C to +85 °C
Battery storage temperature	Recommended max. 30°C

INTERFACE

GNSS antenna	Internal High Gain
Cellular antenna	Internal GSM High Gain
USB	2.0 Micro-USB
LED indication	1 LED
SIM	Micro-SIM
Memory	128MB internal flash memory

FEATURES

Sensors	Accelerometer
Scenarios	Enhanced tamper detection, accelerometer wake up, GNSS, Bluetooth® LE sensors support, Recovery mode, Periodic tracking on stop / on move, Scheduler with time zones, Backup tracking, Static navigation, Lost Bluetooth® LE sensor
Sleep Modes	Single custom sleep mode
Configuration and firmware update	FOTA Web, Teltonika Configurator (USB)
SMS	Configuration, Events, Debug
GPRS commands	Configuration, Debug
Time Synchronization	GNSS, NITZ, NTP

CERTIFICATION & APPROVALS³

Regulatory CE/RED, E-Mark, RCM, UKCA

MAGNETIC HOLDER SPECIFICATIONS

Dimensions 77,5 x 61,5 x 27,5 mm

Material PC + ABS

Operating temperature -40 °C to +80 °C

Flame Classifications
UL94 V-0

Magnets 4 x Neodymium magnets, 20x7mm,
strength: min. 11kg, nickel-plated,
max. operating temp. +80°C

³ Pending

SAFETY INFORMATION

This message contains information on how to operate TAT240 safely. By following these requirements and recommendations, you will avoid dangerous situations. Please read these instructions carefully and follow them strictly before operating the device!



INTERFERENCE

All wireless devices are sensitive to electromagnetic interference, as a result wireless devices might affect the performance of each other.



Be cautious near flammable materials and liquids



USE ONLY ORIGINAL BATTERIES

Using uncertified manufacturer or different type batteries may cause the device to malfunction or even explode



Do not attempt to charge the batteries. Doing so will void the warranty and may cause an explosion.



Battery should not be disposed of with general household waste. Bring damaged or worn-out batteries to your local recycling center or dispose them to battery recycle bin found in stores.



OPERATE THE DEVICE IN SUITABLE CONDITIONS

Comply with local traffic laws, do not operate the device with your hands while driving. Your safety is of utmost importance when you drive.



The programming must be performed using a PC with autonomic power supply.



USE BATTERIES SAFELY

Protect batteries from moisture. Avoid extensive operation at high temperatures.



OTHER

In order to prevent device from mechanical damage it is advisable to transport it in a shock-resistant packaging. If device stopped working properly regardless of the settings only a qualified specialist can help. It is recommended to contact your local seller or your UAB Teltonika Telematics manager in such a case.

CERTIFICATION AND APPROVALS



This sign on the package means that it is necessary to read the User's Manual before your start using the device. Full User's Manual version can be found in our [Wiki](#)¹.

¹ wiki.teltonika-gps.com/index.php?title=TAT240



Hereby, Teltonika declare under our sole responsibility that the above described product is conformity with the relevant Community harmonization: European Directive 2014/53/EU (RED).

-- Refer to Article 10(2). Manufacturers shall ensure that radio equipment shall be so constructed that it can be operated in at least one Member State without infringing applicable requirements on the use of radio spectrum. (Add the following description)



This sign on the package means that all used electronic and electric equipment should not be mixed with general household waste.



The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by UAB Teltonika Telematics is under license. Other trademarks and trade names are those of their respective owners.

CHECK ALL CERTIFICATES

All newest certificates may be found in our [Wiki](#)².

² wiki.teltonika-gps.com/view/TAT240_Certification_%26_Approvals

WARRANTY

We guarantee our products 24-month warranty¹ period.

All batteries carry a 6-month warranty period.

Post-warranty repair service for products is not provided.

If a product stops operating within this specific warranty time, the product can be:

- Repaired
- Replaced with a new product
- Replaced with an equivalent repaired product fulfilling the same functionality
- Replaced with a different product fulfilling the same functionality in case of EOL for the original product

¹ Additional agreement for an extended warranty period can be agreed upon separately.

WARRANTY DISCLAIMER

- Customers are only allowed to return products as a result of the product being defective, due to order assembly or manufacturing fault.
- Products are intended to be used by personnel with training and experience.
- Warranty does not cover defects or malfunctions caused by accidents, misuse, abuse, catastrophes, improper maintenance or inadequate installation – not following operating instructions (including failure to heed warnings) or use with equipment with which it is not intended to be used.
- Warranty does not apply to any consequential damages.
- Warranty is not applicable for supplementary product equipment (i. e. PSU, power cables, antennas) unless the accessory is defective on arrival.
- [More information on what is RMA¹](#)

¹ wiki.teltonika-gps.com/view/RMA_guidelines